



## 6A, AEROX PORTABLE OXYGEN SYSTEM 6 USER, 'A' SYSTEM 6 CU FT

### Specifications

**Part Number:** 6A PORTABLE OXYGEN SYSTEM

**Shipping Box Dimensions:** 12" x 8" x 6"

**Weight:** 3.6 lbs.

#### **CYLINDER**

- DOT approved 3AL/TC lightweight aluminum cylinder
- CGA540 Nickel plated brass valve
- 3000 psi Aerox content gauge
- 5 year hydrostatic test, service life indefinite

#### **REGULATOR**

- CGA540 low profile, fixed flow, single outlet regulator
- External components manufactured of nickel plated aluminum
- Internal components manufactured of CDA360 brass

#### **OXYSAVER CANNULA AND MASK**

- Oxysaver cannula and masks flow meter is measured by altitude with separate readings for cannula and mask
- Flow control valve allows exact adjustment for each individual user
- Oxysaver cannulas extend oxygen duration of a factor of at least four, and are rated for up to 18,000 feet MSL
- Oxygen mask must be used above 18,000 feet MSL (one included with system)
- Quick disconnect fittings allow for fast one handed connection to regulator



### **OTHER CONFIGURATIONS BY SPECIAL REQUEST**

