



# PRO-O2-( ) EMERGENCY OXYGEN SYSTEM



## Specifications

**Part Number:** PRO-O2-( )  
 (-2) 2 Cubic Feet  
 (-4) 4 Cubic Feet  
 (-6) 6 Cubic Feet

### **Dimensions:**

Height: See Table  
 Width: See Table  
 Weight: See Table  
 Duration: See Table

**Description:** Aluminum Cylinders Per DOT 3AL 2216 & TC3-ALM Nickel Plated Brass Regulator With Viton O-Ring Seals and MS22066 Capped Filler.

### **Maintenance:**

Cylinder: 5 year Hydro-Static Test.  
 Regulator: 5 Year Overhaul (Recommended)  
 Unlimited service life.

PRO-O2 Emergency Oxygen Systems are pull cable activated. By pulling the Mask to the three foot hose length, a key is pulled from the regulator, initiating a 2.5 liter per minute flow to the mask. The key may be quickly reinserted to stop the oxygen flow.

**Accessories:** Equipped with MSKA Economy Re-breather Mask (Vinyl) or High End MSK-AS Re-breather Mask (Silicone).

## **Dimensional Table**

<b>Part Number</b>	<b>A (Height)</b>	<b>B (Diameter) (Cylinder)</b>	<b>C (Weight)</b>	<b>Duration</b>
<b>PRO-O2-2</b>	<b>8.5 Inches</b> (21.6 cm)	<b>2.5 Inches</b> (6.4 cm)	<b>1.8 Lbs</b> (0.8 Kg)	<b>17 Minutes</b>
<b>PRO-O2-4</b>	<b>11 Inches</b> (27.9 cm)	<b>3.25 Inches</b> (8.3 cm)	<b>2.6 Lbs</b> (1.2 Kg)	<b>40 Minutes</b>
<b>PRO-O2-6</b>	<b>14 Inches</b> (35.6 cm)	<b>3.25 Inches</b> (8.3 cm)	<b>3.4 Lbs</b> (1.5 Kg)	<b>60 Minutes</b>